


Features

- Epitaxial Planar Die Construction.
- NPN complement:MMBT2222A
- Ideal for Medium Power Amplification and Switching.
- Marking Code:2F



SOT-23		
Dim	Min	Max
A	0.37	0.51
B	1.20	1.40
C	2.30	2.50
D	0.89	1.03
E	0.45	0.60
G	1.78	2.05
H	2.80	3.00
J	0.013	0.10
K	0.903	1.10
L	0.45	0.61
M	0.085	0.180
α	0°	8°
All Dimensions in mm		

Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Rating	Symbol	Max	Unit
Collector-Emitter Voltage	V _{CEO}	-60	V
Collector-Base Voltage	V _{CBO}	-60	V
Emitter-Base Voltage	V _{EBO}	-5	V
Collector Current	I _C	-600	mA

• THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR-5 Board,(1) T _A =25°C Derate above 25°C	PD	225 1.8	mW mW/°C
Thermal Resistance,Junction to Ambient	R _{θJA}	556	°C/W
Total Device Dissipation Alumina Substrate,(2) T _A =25°C Derate above 25°C	PD	300 2.4	mW mW/°C
Thermal Resistance,Junction to Ambient	R _{θJA}	417	°C/W
Junction and Storage Temperature	T _j , T _{stg}	-55 to +150	°C

1. FR-5 = 1.0 x 0.75 x 0.062 in.

2. Alumina = 0.4 x 0.3 x 0.024 in. 99.5% alumina.

Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

OFF CHARACTERISTICS

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Collector–Emitter Breakdown Voltage ($I_C = -10\text{ mA}$, $I_B = 0$)	$V_{BR}(CEO)$	-60	-	-	V
Collector–Base Breakdown Voltage ($I_C = -10\text{ }\mu\text{A}$, $I_E = 0$)	$V_{BR}(CBO)$	-60	-	-	V
Emitter–Base Breakdown Voltage ($I_E = -10\text{ }\mu\text{A}$, $I_C = 0$)	$V_{BR}(EBO)$	-5	-	-	V
Collector Cutoff Current ($V_{CE} = -30\text{ V}$, $V_{BE} = -0.5\text{ V}$)	I_{CEX}	-	-	-50	nA
Collector Cutoff Current ($V_{CB} = -50\text{ V}$, $I_E = 0$) ($V_{CB} = -50\text{ V}$, $I_E = 0$, $T_A = 125^\circ\text{C}$)	I_{CBO}	-	-	-0.01 -10	μA
Base Cutoff Current ($V_{CE} = -30\text{ V}$, $V_{BE} = -0.5\text{ V}$)	I_{BL}	-	-	-50	nA

ON CHARACTERISTICS (Note 2.)

DC Current Gain ($I_C = -0.1\text{ mA}$, $V_{CE} = -10\text{ V}$) ($I_C = -1.0\text{ mA}$, $V_{CE} = -10\text{ V}$) ($I_C = -10\text{ mA}$, $V_{CE} = -10\text{ V}$) ($I_C = -150\text{ mA}$, $V_{CE} = -10\text{ V}$) ($I_C = -500\text{ mA}$, $V_{CE} = -10\text{ V}$)	HFE	75 100 100 100 50	- - - - -	- - - 300 -	
Collector–Emitter Saturation Voltage ($I_C = -150\text{ mA}$, $I_B = -15\text{ mA}$) ($I_C = -500\text{ mA}$, $I_B = -50\text{ mA}$)	$V_{CE}(\text{sat})$	- -	- -	-0.4 -1.6	V
Base–Emitter Saturation Voltage ($I_C = -150\text{ mA}$, $I_B = -15\text{ mA}$) ($I_C = -500\text{ mA}$, $I_B = -50\text{ mA}$)	$V_{BE}(\text{sat})$	- -	- -	-1.3 -2.6	V

SMALL–SIGNAL CHARACTERISTICS


Current–Gain — Bandwidth Product ($I_C = -50\text{ mA}$, $V_{CE} = -20\text{ V}$, $f = 100\text{ MHz}$)	f_T	200	-	-	MHz
Output Capacitance ($V_{CB} = -10\text{ V}$, $I_E = 0$, $f = 1.0\text{ MHz}$)	C_{obo}	-	-	8	pF
Input Capacitance ($V_{EB} = -2\text{ V}$, $I_C = 0$, $f = 1.0\text{ MHz}$)	C_{ibo}	-	-	30	pF

SWITCHING CHARACTERISTICS

Turn–On Time	(VCC = -30 V, $I_C = -150\text{ mA}$, $I_{B1} = -15\text{ mA}$)	t_{on}	-	-	45	ns
Delay Time		t_d	-	-	10	
Rise Time		t_r	-	-	40	
Turn–Off Time	(VCC = -6 V, $I_C = -150\text{ mA}$, $I_{B1} = I_{B2} = -15\text{ mA}$)	t_{off}	-	-	100	
Storage Time		t_s	-	-	80	
Fall Time		t_f	-	-	30	

2. Pulse Test: Pulse Width $\leq 300\text{ }\mu\text{s}$, Duty Cycle $\leq 2.0\%$.

TYPICAL TRANSIENT CHARACTERISTICS



IMPORTANT NOTICE

HC-SEMI reserves the right to make changes without further notice to any products herein.

HC-SEMI makes no warranty, representation or guarantee regarding

The suitability of its products for any particular purpose, nor does HC-SEMI assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages.

“Typical” parameters can and do vary in different applications. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts.

HC-SEMI products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the HC-SEMI product could create a situation where personal injury or death may occur.

Should Buyer purchase or use HC-SEMI products for any such unintended or unauthorized application, Buyer shall indemnify and hold HC-SEMI and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that HC-SEMI was negligent regarding the design or manufacture of the part.