




Features

- Complementary to S9014.
- We declare that the material of product compliance with RoHS requirements.
- Marking Code:M6



SOT-23		
Dim	Min	Max
A	0.37	0.51
B	1.20	1.40
C	2.30	2.50
D	0.89	1.03
E	0.45	0.60
G	1.78	2.05
H	2.80	3.00
J	0.013	0.10
K	0.903	1.10
L	0.45	0.61
M	0.085	0.180
α	0°	8°
All Dimensions in mm		

Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Value	Unit
Collector Base Voltage	V_{CBO}	-50	V
Collector Emitter Voltage	V_{CEO}	-45	V
Emitter Base Voltage	V_{EBO}	-5	V
Collector Current	I_C	-100	mA
Power Dissipation	P_{tot}	300	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{Stg}	- 55 to + 150	$^\circ\text{C}$

Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified


OFF CHARACTERISTICS

Characteristic	Symbol	Min	Typ	Max	Unit
Collector-Emitter Breakdown Voltage ($I_C = -1.0\text{mA}$)	$V_{(BR)CEO}$	-45	-	-	V
Emitter-Base Breakdown Voltage ($I_E = -100\mu\text{A}$)	$V_{(BR)EBO}$	-5	-	-	V
Collector-Base Breakdown Voltage ($I_C = -100\mu\text{A}$)	$V_{(BR)CBO}$	-50	-	-	V
Collector Cutoff Current ($V_{CB} = -40\text{V}$)	I_{CBO}	-	-	-100	nA
Emitter Cutoff Current ($V_{EB} = -3\text{V}$)	I_{EBO}	-	-	-100	nA

ON CHARACTERISTICS

DC Current Gain ($I_C = -1\text{mA}$, $V_{CE} = -5\text{V}$)	S9015B	HFE	100	-	220	
	S9015C	HFE	200	-	450	
	S9015D	HFE	400	-	800	
Collector-Emitter Saturation Voltage ($I_C = -100\text{mA}$, $I_B = -10\text{mA}$)	VCE	-	-	-0.3	V	

TYPICAL TRANSIENT CHARACTERISTICS



IMPORTANT NOTICE

HC-SEMI reserves the right to make changes without further notice to any products herein.

HC-SEMI makes no warranty, representation or guarantee regarding

The suitability of its products for any particular purpose, nor does HC-SEMI assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages.

“Typical” parameters can and do vary in different applications. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts.

HC-SEMI products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the HC-SEMI product could create a situation where personal injury or death may occur.

Should Buyer purchase or use HC-SEMI products for any such unintended or unauthorized application, Buyer shall indemnify and hold HC-SEMI and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that HC-SEMI was negligent regarding the design or manufacture of the part.